

Nigeria Market		
basic information	brand	
	sub-brand	
	brand in market	
	model	BJ5089VEBEA-FA
	product platform	3.0t
body	model	L1995
	type	Single row seat tiltable
Whole vehicle main dimensions	Overall dimensions (LxWxH)mm	6995×2250×2350
	chassis dimensions (LxWxH)mm	6725×2100×2280
	Inner dimensions of the cargo body (LxWxH)mm	5150×2050×550
	Wheel track (front/rear) (mm)	1685/1615
	Wheel base (mm)	3800
Weight data	Gross vehicle weight (kg)	8495
	Curb weight (kg)	3650
	Rated payload (kg)	4650
	Persons in cab (persons)	3
Whole vehicle main performance	Max. speed (km/h)	95
	Max. slope of climb (%)	30
	Fuel consumption (L/100km)	14.7
	Min. turning diameter (m)	16
	min. ground clearance (mm)	180
Engine	model	ISF3.8s3141 (105) (机械泵)
	Type	Four-cylinder、In-line、Fourstroke、Water-cooling
	Displacement (L)	3.76
	Rated power (kw/rpm)	105/2600
	Max torque (N.m/rpm)	450/1200-2200
	emission stadard	EURO. III
	supplier	FOTON&CUMMINS
ClutchGearbox	Gearbox Model	651B
	Speed ratio	5.513/3.417/2.115/1.381/1/0.79 5/5.128
	PTO/PTO Connector	PTO Connector
	Supplier	wanliyang

	cluth model	diaphragm springΦ325×Φ210mm
	PTO	×
chassis main performance	Front axle Model	Forging h-beam
	Rated load (T)	2.5
	Rear axle Model	monolithic construction
	Rated load (T)	6t
	gear ratio	4.875
	Tyre model	8.25R16
	Quantity	6+1
	Steering gear	Circular ball type
	Type	Power steering
	Front suspension	non-independent suspension
	Leaf spring number	9

	Rear suspension	non-independent suspension
	Leaf spring number	11+7
	Cubage (L):	200
Brake system	Service brake	Pneumatic drum brake
	Parking brake	air brake
	Auxiliary brake	Exhaust brake
	ABS	×
	loading sensing pressure proportioning valve	●
Electrical system	Rated voltage (V) :	24
	Battery	100AH*2
Product configuration	Heater	●
	Adjustable steering wheel	●
	Electric flameout	●
	double sun shield	●
	battery cover	●
	moonwatch telescope	●
	belw side endoscopic	●
	A/C	×
	Center control lock	×
	Electro-driven window glass lifter	×
	Radar	×
	Cruise	×
	radio	●
	AUX:	×
MP3:	●	

	CD:	×
	Multimedia Audio	×
	Traveling data recorder	×
	deflector	○
basic equipment ○ optional equipment — without equipme		